

Model #: 6050-Silver

UPC: 649532760503

**MSRP:** \$14.99



The CyberPower 6050-SILVER surge suppressor is an all-purpose electronic surge protector with one built-in RJ-11 port and 900 joule MOV technology, RJ-11 ports allow for protection of telecommunication devices such as phones, faxes. modems, and DSL lines, while MOV technology safely guards the surge protector and connected electronics against line abnormalities and lightning surges. This surge protector is ideal for personal computers, stereo electronics, phones/answering machines, and all other consumer electronics. The 6050 is also equipped with EMI/RFI filters that block unwanted line noise from all connected electronics. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$45,000.

- MOV (Metal Oxide Varistor) MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Surge Protector Outlets Widely spaced outlets allow you to conveniently add large transformerbased plugs without compromising the utility of other outlets.
- EMI/RFI Shielding Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications All CyberPower's manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Keyhole Mounting Slots Convenient mounting slots are located on the back on the surge protector.
- Sturdy ABS Case Constructed of impact-resistant composite material for maximum durability.

## **Technical Specifications**

Input	General	
Input		6050-SII VEP
Voltage	Widdel #	0030-SIEVEIX
Voltage	Input	
Plug Style         Right-angle           Cord Length         4 ft           Output         6           Outlets - Total         6           Outlets - Widely Spaced         1 x NEMA 5-15R           Outlets - Normal Spaced         5 x NEMA 5-15R           Surge Protection and Filtering         Surge Suppression           Burge Suppression         900 Joules           Phone Protection (RJ11)         One-in/One-out           Ethernet Protection (RJ45)         None           Coax Protection (RG6)         None           Maximum Surge Current         45,000 Amps           Maximum Surge Current H-N         15,000 Amps           Maximum Surge Current N-G         15,000 Amps           Maximum Surge Voltage         6,0000V           Clamping Voltage         330 V           Response Time         41 ns           EMI/RFI Filtration         EMI/RFI 150KHz to 100MHz           Attenuation         Up to 58dB           Indicators         Power (Red); Surge (Red)           Indicator Lights         Power (Red); Surge (Red)           Weight         0.9375 lbs.           Color         Black/Silver           Warranty         Lifetime           Connected Equipment Guarantee <td< td=""><td>Voltage</td><td>110/120V Nominal</td></td<>	Voltage	110/120V Nominal
Plug Style         Right-angle           Cord Length         4 ft           Output         6           Outlets - Total         6           Outlets - Widely Spaced         1 x NEMA 5-15R           Outlets - Normal Spaced         5 x NEMA 5-15R           Surge Protection and Filtering         Surge Suppression           Burge Suppression         900 Joules           Phone Protection (RJ11)         One-in/One-out           Ethernet Protection (RJ45)         None           Coax Protection (RG6)         None           Maximum Surge Current         45,000 Amps           Maximum Surge Current H-N         15,000 Amps           Maximum Surge Current N-G         15,000 Amps           Maximum Surge Voltage         6,0000V           Clamping Voltage         330 V           Response Time         41 ns           EMI/RFI Filtration         EMI/RFI 150KHz to 100MHz           Attenuation         Up to 58dB           Indicators         Power (Red); Surge (Red)           Indicator Lights         Power (Red); Surge (Red)           Weight         0.9375 lbs.           Color         Black/Silver           Warranty         Lifetime           Connected Equipment Guarantee <td< td=""><td>Plug Type</td><td>NEMA 5-15P</td></td<>	Plug Type	NEMA 5-15P
Output       Outlets - Total     6       Outlets - Widely Spaced     1 x NEMA 5-15R       Outlets - Normal Spaced     5 x NEMA 5-15R       Surge Protection and Filtering     900 Joules       Surge Suppression     900 Joules       Phone Protection (RJ11)     One-in/One-out       Ethernet Protection (RJ45)     None       Coax Protection (RG6)     None       Maximum Surge Current     45,000 Amps       Maximum Surge Current H-N     15,000 Amps       Maximum Surge Current N-G     15,000 Amps       Maximum Surge Voltage     6,000V       Clamping Voltage     330 V       Response Time     <1 ns	Plug Style	Right-angle
Outlets - Total         6           Outlets - Widely Spaced         1 x NEMA 5-15R           Outlets - Normal Spaced         5 x NEMA 5-15R           Surge Protection and Filtering         900 Joules           Surge Suppression         900 Joules           Phone Protection (RJ11)         One-in/One-out           Ethernet Protection (RG6)         None           Maximum Surge Current         45,000 Amps           Maximum Surge Current H-N         15,000 Amps           Maximum Surge Current N-G         15,000 Amps           Maximum Surge Voltage         6,000V           Clamping Voltage         330 V           Response Time         <1 ns	Cord Length	4 ft
Outlets - Total         6           Outlets - Widely Spaced         1 x NEMA 5-15R           Outlets - Normal Spaced         5 x NEMA 5-15R           Surge Protection and Filtering         900 Joules           Surge Suppression         900 Joules           Phone Protection (RJ11)         One-in/One-out           Ethernet Protection (RG6)         None           Maximum Surge Current         45,000 Amps           Maximum Surge Current H-N         15,000 Amps           Maximum Surge Current N-G         15,000 Amps           Maximum Surge Voltage         6,000V           Clamping Voltage         330 V           Response Time         <1 ns		
Outlets - Widely Spaced         1 x NEMA 5-15R           Outlets - Normal Spaced         5 x NEMA 5-15R           Surge Protection and Filtering         900 Joules           Surge Suppression         900 Joules           Phone Protection (RJ11)         One-in/One-out           Ethernet Protection (RG6)         None           Coax Protection (RG6)         None           Maximum Surge Current         45,000 Amps           Maximum Surge Current H-N         15,000 Amps           Maximum Surge Current N-G         15,000 Amps           Maximum Surge Voltage         6,000V           Clamping Voltage         330 V           Response Time         <1 ns	Output	
Surge Protection and Filtering Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None Coax Protection (RG6) None Maximum Surge Current 45,000 Amps Maximum Surge Current H-N 15,000 Amps Maximum Surge Current H-G 15,000 Amps Maximum Surge Current N-G 15,000 Amps Maximum Surge Voltage 6,000V Clamping Voltage 330 V Response Time <1 ns EMI/RFI Filtration EMI/RFI 150KHz to 100MHz Attenuation Up to 58dB  Indicators Indicator Lights Power (Red); Surge (Red)  Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver  Warranty Product Warranty Lifetime Connected Equipment Guarantee	Outlets - Total	6
Surge Protection and Filtering  Surge Suppression 900 Joules  Phone Protection (RJ11) One-in/One-out  Ethernet Protection (RJ45) None  Coax Protection (RG6) None  Maximum Surge Current 45,000 Amps  Maximum Surge Current H-G 15,000 Amps  Maximum Surge Current N-G 15,000 Amps  Maximum Surge Voltage 6,000V  Clamping Voltage 330 V  Response Time <1 ns  EMI/RFI Filtration EMI/RFI 150KHz to 100MHz  Attenuation Up to 58dB  Indicators  Indicator Lights Power (Red); Surge (Red)  Physical  Dimensions (WxHxD) 11.5" x 2" x 1.5"  Weight 0.9375 lbs.  Color Black/Silver  Warranty  Product Warranty  Lifetime  Lifetime  Lifetime	Outlets - Widely Spaced	1 x NEMA 5-15R
Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None  Coax Protection (RG6) None  Maximum Surge Current 45,000 Amps  Maximum Surge Current H-N 15,000 Amps  Maximum Surge Current H-G 15,000 Amps  Maximum Surge Current N-G 15,000 Amps  Maximum Surge Voltage 6,000V  Clamping Voltage 330 V  Response Time <1 ns  EMI/RFI Filtration EMI/RFI 150KHz to 100MHz  Attenuation Up to 58dB  Indicators  Indicator Lights Power (Red); Surge (Red)  Physical  Dimensions (WxHxD) 11.5" x 2" x 1.5"  Weight 0.9375 lbs.  Color Black/Silver  Warranty  Product Warranty Lifetime  Connected Equipment Guarantee	Outlets - Normal Spaced	5 x NEMA 5-15R
Surge Suppression 900 Joules Phone Protection (RJ11) One-in/One-out Ethernet Protection (RJ45) None  Coax Protection (RG6) None  Maximum Surge Current 45,000 Amps  Maximum Surge Current H-N 15,000 Amps  Maximum Surge Current H-G 15,000 Amps  Maximum Surge Current N-G 15,000 Amps  Maximum Surge Voltage 6,000V  Clamping Voltage 330 V  Response Time <1 ns  EMI/RFI Filtration EMI/RFI 150KHz to 100MHz  Attenuation Up to 58dB  Indicators  Indicator Lights Power (Red); Surge (Red)  Physical  Dimensions (WxHxD) 11.5" x 2" x 1.5"  Weight 0.9375 lbs.  Color Black/Silver  Warranty  Product Warranty Lifetime  Connected Equipment Guarantee		
Phone Protection (RJ11)  Ethernet Protection (RJ45)  Coax Protection (RG6)  Maximum Surge Current  Maximum Surge Current H-N  Maximum Surge Current H-G  Maximum Surge Current N-G  Maximum Surge Voltage  Clamping Voltage  Clamping Voltage  EMI/RFI Filtration  Attenuation  Indicators  Indicator Lights  Physical  Dimensions (WxHxD)  Product Warranty  Product Warranty  Product Warranty  Connected Equipment Guarantee  None  45,000 Amps  45,000 Amps	Surge Protection and Filtering	
Ethernet Protection (RJ45)  Coax Protection (RG6)  Maximum Surge Current  Maximum Surge Current H-N  Maximum Surge Current H-G  Maximum Surge Current H-G  Maximum Surge Current N-G  Maximum Surge Current N-G  Maximum Surge Voltage  Maximum Surge Voltage  Clamping Voltage  Clamping Voltage  Salo V  Response Time  EMI/RFI Filtration  EMI/RFI 150KHz to 100MHz  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  O.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Surge Suppression	900 Joules
Coax Protection (RG6)  Maximum Surge Current  45,000 Amps  Maximum Surge Current H-N  15,000 Amps  Maximum Surge Current H-G  15,000 Amps  Maximum Surge Current N-G  15,000 Amps  Maximum Surge Current N-G  15,000 Amps  Maximum Surge Voltage  6,000V  Clamping Voltage  330 V  Response Time  41 ns  EMI/RFI Filtration  EMI/RFI Filtration  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Phone Protection (RJ11)	One-in/One-out
Maximum Surge Current  Maximum Surge Current H-N  15,000 Amps  Maximum Surge Current H-G  15,000 Amps  Maximum Surge Current N-G  15,000 Amps  Maximum Surge Current N-G  15,000 Amps  Maximum Surge Voltage  6,000V  Clamping Voltage  330 V  Response Time  EMI/RFI Filtration  EMI/RFI 150KHz to 100MHz  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Ethernet Protection (RJ45)	None
Maximum Surge Current H-N  Maximum Surge Current H-G  Maximum Surge Current N-G  Maximum Surge Current N-G  Maximum Surge Voltage  6,000V  Clamping Voltage  Response Time  EMI/RFI Filtration  EMI/RFI 150KHz to 100MHz  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Coax Protection (RG6)	None
Maximum Surge Current H-G  Maximum Surge Current N-G  Maximum Surge Voltage  6,000V  Clamping Voltage  Response Time  EMI/RFI Filtration  EMI/RFI Filtration  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Maximum Surge Current	45,000 Amps
Maximum Surge Current N-G  Maximum Surge Voltage  6,000V  Clamping Voltage  330 V  Response Time  <1 ns  EMI/RFI Filtration  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee  135,000 Amps  6,000V  105,000 Amps  105,00	Maximum Surge Current H-N	15,000 Amps
Maximum Surge Voltage 6,000V  Clamping Voltage 330 V  Response Time <1 ns  EMI/RFI Filtration EMI/RFI 150KHz to 100MHz  Attenuation Up to 58dB  Indicators  Indicator Lights Power (Red); Surge (Red)  Physical  Dimensions (WxHxD) 11.5" x 2" x 1.5"  Weight 0.9375 lbs.  Color Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Maximum Surge Current H-G	15,000 Amps
Clamping Voltage  Response Time  <1 ns  EMI/RFI Filtration  EMI/RFI 150KHz to 100MHz  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Connected Equipment Guarantee  Lifetime  Connected Equipment Guarantee	Maximum Surge Current N-G	15,000 Amps
Response Time  EMI/RFI Filtration  EMI/RFI 150KHz to 100MHz  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee	Maximum Surge Voltage	6,000V
EMI/RFI Filtration  Attenuation  Up to 58dB  Indicators  Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Connected Equipment Guarantee  Lifetime	Clamping Voltage	330 V
Attenuation Up to 58dB  Indicators  Indicator Lights Power (Red); Surge (Red)  Physical  Dimensions (WxHxD) 11.5" x 2" x 1.5"  Weight 0.9375 lbs.  Color Black/Silver  Warranty  Product Warranty Lifetime  Connected Equipment Guarantee Lifetime	Response Time	<1 ns
Indicators Indicator Lights Power (Red); Surge (Red)  Physical Dimensions (WxHxD) 11.5" x 2" x 1.5" Weight 0.9375 lbs. Color Black/Silver  Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime	EMI/RFI Filtration	EMI/RFI 150KHz to 100MHz
Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee  Lifetime	Attenuation	Up to 58dB
Indicator Lights  Power (Red); Surge (Red)  Physical  Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee  Lifetime		
Physical  Dimensions (WxHxD)		
Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee  Lifetime	Indicator Lights	Power (Red); Surge (Red)
Dimensions (WxHxD)  11.5" x 2" x 1.5"  Weight  0.9375 lbs.  Color  Black/Silver  Warranty  Product Warranty  Lifetime  Connected Equipment Guarantee  Lifetime	Physical	
Weight 0.9375 lbs.  Color Black/Silver  Warranty  Product Warranty Lifetime  Connected Equipment Guarantee Lifetime		44 E" × 2" × 4 E"
Color Black/Silver  Warranty Product Warranty Lifetime Connected Equipment Guarantee Lifetime		
Warranty Product Warranty Connected Equipment Guarantee Lifetime		
Product Warranty Lifetime  Connected Equipment Guarantee Lifetime	Color	Black/Silver
Product Warranty Lifetime  Connected Equipment Guarantee Lifetime	Warranty	
Connected Equipment Guarantee Lifetime		Lifetime
	CEG Amount	\$45,000